

Application Number: 09/956,185

Docket: 6464.01

---

IN THE CLAIMS

---

1.-21. (Previously Cancelled)

22. (Previously Added) A method for analyzing body fluids, in which a body fluid is accessed for analysis via an implantable means for accessing the fluid, said means comprising a port body implanted in a patient's body, a portion of the port body extending through the skin, said port body comprising a tube arrangement extending into the interior of the body, wherein a test sensor is inserted into the interior of the body via said tube arrangement, and wherein a body fluid is analyzed by the sensor at an intermediate site of said tube arrangement, the body fluid being aspirated to said intermediate site.

23. (Cancel)

24. (Currently Amended) The method of claim ~~23~~ 22, further comprising anchoring the port body into a portion of skin on the body .

25. (Currently Amended) The method of claim ~~23~~ 22, wherein aspirating the body fluids further comprises introducing an aspiration catheter through the first tube to aspirate the body fluids.

26. (Previously Added) The method of claim 25 wherein the body fluids are extracted external to the body and wherein analyzing the body fluids occurs external to the body.

27. (Previously Added) The method of claim 25, wherein the aspiration catheter is passed through a self-closing diaphragm located within the port body.

28. (Currently Amended) The method of claim ~~23~~ 22, further comprising introducing a medicament through a second tube coupled with the port body.

29. (Previously Added) The method of claim 27, wherein the medicament is introduced through a feed catheter inserted through the second tube.

Application Number: 09/938,185

Docket: 6464.01

- 
30. (Previously Added) The method of claim 29, wherein the feed catheter is passed through a self-closing diaphragm located within the port body.
31. (Currently Amended) The method of claim ~~23~~ 22, further comprising inserting a probe through the first tube to contact the body fluid.
32. (Previously Added) The method of claim 31, wherein the probe is a test strip.
33. (Previously Added) The method of claim 31, wherein the probe detects the concentration and/or existence of a substance.
34. (Previously Added) The method of claim 31, wherein the probe is a microdialysis probe.
35. (Currently Amended) The method of claim ~~23~~ 22, wherein a testing device is permanently mounted within the implantable device.
36. (Currently Amended) The method of claim 35, wherein the testing device is located within the first tube arrangement.
37. (Previously Added) The method of claim 35, wherein the testing device includes an electronic test sensor.
38. (Previously Added) The method of claim 37, wherein the electronic test sensor includes one or more connecting wires passing through the port body, external to the body.
39. (Previously Added) The method of claim 38, wherein the connecting wires are coupled with a working electrode, a counter-electrode and a zero current electrode.

Application Number: 09/958,185

Docket: 6464.01

40. (Previously Added) A method of testing body fluids and introducing a medicament comprising:

implanting a port body into a body, the port body having a selectively accessible exposed portion external to the body, an aspiration tube depending from the port body and in contact with a source of body fluids, and a feed tube depending from the port body;

passing a medicament through the selectively accessible exposed portion and into the feed tube, wherein the medicament is introduced to the body upon exiting the feed tube; and

aspirating body fluids in the aspiration tube wherein the body fluids are tested to determine presence and/or concentration of an element within the body fluid.

41. (Previously Added) The method of claim 40, wherein the selectively accessible exposed portion is a self closing diaphragm.

42. (Previously Added) The method of claim 40, wherein passing a medicament further comprises introducing a feed catheter through the selectively accessible exposed portion .

43. (Previously Added) The method of claim 40, wherein aspirating body fluids further comprises introducing an aspirating catheter through the selectively accessible exposed portion and passing the aspirating catheter through the aspirating tube until the aspirating catheter contacts body fluids.

44. (Previously Added) The method of claim 43, wherein the body fluids are extracted from the body through the aspirating catheter so that the testing of the body fluids is performed external to the body.

45. (Previously Added) The method of clam 40 wherein the body fluids are tested within the aspiration tube.

46. (Previously Added) A method for analyzing body fluids, comprising the steps of:

implanting a port body in the patient body, said port body extending through the skin of the patient body and being secured in place by a anchoring section located in or under the skin,

Application Number: 09/938,185

Docket: 6464.01

said port body having a shaft with an elastic self-closing diaphragm therein and a tube arrangement extending into the interior of the patient body from the self-closing diaphragm; accessing body fluids through the implanted port body; and analyzing the body fluids encountered at a test site within the patient body.

47. (Previously Added) The method as set forth in claim 46, wherein the step of accessing body fluids further comprises the step of routing an aspiration catheter from a point outside the patient body, through the self-closing diaphragm and into the tube arrangement.

48. (Previously Added) The method as set forth in claim 47, wherein the aspiration catheter is used to withdraw a body fluid from the test site to a point outside the patient body, the body fluid then being analyzed at a remote location.

49. (Previously Added) The method as set forth in claim 47, wherein the aspiration catheter is used to aspirate a body fluid to the test site where a sensor or probe then encounters the body fluid.

50. (Previously Added) The method as set forth in claim 46, wherein the step of accessing body fluids further comprises the step of routing a probe from a point outside the patient body, through the self-closing diaphragm and into the tube arrangement.

51. (Previously Added) The method as set forth in claim 50, wherein the probe is a microdialysis probe.

52. (Previously Added) The method as set forth in claim 46, wherein the step of accessing body fluids further comprises the step of routing a sensor from a point outside the patient body, through the self-closing diaphragm and into the tube arrangement.

53. (Previously Added) The method as set forth in claim 52, wherein the shaft is made of a metallic material and acts as a reference or counter electrode for the sensor.

Application Number: 09/958,185

Docket: 6464.01

---

54. (Previously Added) The method as set forth in claim 52, wherein the sensor remains at the test site for continuous testing.

55. (Previously Added) The method as set forth in claim 52, wherein body fluid is aspirated to the test site, the sensor being located at the test site.